



**SPECIFICATION >** ASCENTI's World of One custom wall sign, PICASSO. Named for one of several conference rooms at the Hyatt Regency Chicago for which it was developed, PICASSO is a stylish and striking wayfinding beacon for guests. Each fixture features a custom laser-cut aluminum text block, highlighted by a subtly frosted acrylic panel that seemingly glows from within. Text may be double-sided or single-sided (for locations where opposite text is not needed for navigation). The linear 3ft form is standard as cantilevered wall mounted, but may be specified as a ceiling mount with two vertical arm-mounts at each end. ASCENTI's renowned customization ability means our engineering team can modify this signage to suit any vision. Please provide specification details, as well as dimming and control specifications, so we may present a custom design solution that meets your project needs.

**ENVIRONMENTS >** Hospitality, Corporate Offices, Retail and Entertainment Venues.

**LED >** ASCENTI's own VIVIO™ LED Series offers advanced engineering utilizing the latest LED technology:

**AscendLED™** - Ideal for retail, entertainment and daytime use environments at 95+ CRI. *4.4W or 6.5W/FT*

**Circadian-Safe™** - Patented Violet chip emission to achieve the highest CRI available at 98+. Ideal for the home environment to assist our human circadian rhythm. *4.4W or 6.5W/FT*

**HLE™ High Lumen Efficacy** - Meet ASCENTI's next evolution in high-performance LEDs. Our HLE tape boasts an increase of approximately 100 lumens per foot, with only a minimal increase in energy usage @5W/FT.

**RGBWW (5-in-1 Red-Green-Blue-Double White)** - Combines two white LEDs, one warm and one cool, achieving a wider color spectrum. Separate DMX controls required. *8.5W/FT*

**TW Tunable White Circadian-Safe™** - Allows precise color temperature control in an effort to safely maintain our natural circadian rhythm. Dual BLUE and VIOLET chip design. Separate DMX controls required. *6.5W/FT*

**PTW Dim-to-Warm Circadian-Safe™** - Simple, smooth dimming to full off while simultaneously reducing CRI to warmer tones. Dual integrated Blue/Violet chip design. Eliminates the need for additional color controllers.

**CONSTRUCTION >** Sturdy steel and aluminum frame with a 1/2" thick composite of polished acrylic. Wall mount plate provided (hardware by others). If specified as ceiling mount, two arms with canopy and mount plates provided. Drivers shall be remote and require engineering consultation to ensure proper loading. Contact factory if driver enclosure is required. Flex conduit by others. All electrical components are installed, wired and 100% tested prior to shipping.

**MOUNTING >** Wall mount.

**FINISH >** Powdercoat finish is standard, medium silver. Custom colors are available - consult factory.

**RATED >** Suitable for Damp/Dry Location.

**WARRANTY >** 5 years.

**AS THIS IS A CUSTOM WORLD OF ONE ASCENTI LUMINAIRE, SUBMITTALS ARE REQUIRED.**

Type: Qty: Project:

<b>PIC</b>	<b>PICASSO - CUSTOM LINEAR SIGN</b>	
<b>Width</b>		
3	3 FT nominal	
C_____	Custom width	
<b>Diffuser</b>		
FR	Frosted acrylic panel	
<b>Text</b>		
S	Single-sided	
D	Double-sided	
<b>Linear CCT - Color Temperature</b>		
27A	2700°K AscendLED™	
30A	3000°K AscendLED™	
40A	4000°K AscendLED™	
50A	5000°K AscendLED™	
27CS	2700°K Circadian-Safe™	
30CS	3000°K Circadian-Safe™	
40CS	4000°K Circadian-Safe™	
27HLE	2700°K HLE™ High Lumen Efficacy	
40HLE	4000°K HLE™ High Lumen Efficacy	
RWW	RGBWW (5-in-1 Red-Green-Blue-Warm White-Cool White)	
T3018	Tunable White Circadian-Safe™ BLU30A-VIO18CS	
T5027	Tunable White Circadian-Safe™ BLU50A-VIO27CS	
T6527	Tunable White Circadian-Safe™ BLU65A-VIO27CS	
PW3018	PTW Dim-to-Warm Circadian-Safe™ BLU30A-VIO18CS	
PW4027	PTW Dim-to-Warm Circadian-Safe™ BLU40A-VIO27CS	
CK_____	Custom Kelvin (contact factory)	

**Linear Output (per foot)**

4.4	4.4 Watts/LF ("A" or "CS" single CCT, or Tunable)
6.1	6.1 Watts/LF ("PW" Dim-to-Warm)
6.5	6.5 Watts/LF ("A" single CCT or Tunable)
8.5	8.5 Watts/LF (RGBWW only)

**Control**

010	0-10V Dimmable Driver
ELV	ELV Triac Dimmable Driver
5in1	5-in-1 ELV/0-10V Dimmable Driver
DMX	DMX Control (consult factory)
DAL	Dali Dimming
LUT	Lutron Ecosmart Dimming (consult factory)

**Mounting**

WM	Wall Mount
SM	Surface/Ceiling Mount (armature)
CM_____	Custom mount solution

**Finish**

SVM	Medium Silver Powdercoat
CC_____	Custom RAL color (consult factory)

Enter desired text cut-out:

Example:

This custom specification sheet is considered a "representation" of ASCENTI Lighting's custom OEM capabilities and is subject to change. ASCENTI may remove or discontinue any option, at any time, for any reason.

