



APPLICATIONS > At a mere 1.25" square, the SlimJim exterior bollard offers a sleek, unobtrusive and modern accent landscaping profile. Ideal for pathway, area accents and mounting between or adjacent to exterior stair rails, fence posts, trees or walls. Adjustable LED head rotates vertically 118.5° for precise aiming (28.5° up and 90° down). Heavy-duty ground spike included.

LED > 25-degree narrow spot distribution. 3W Cree XPE LED, 80+ CRI, 90 lumens, PMMA diffuser, IP67. DC12V-24V input voltage.
CCT: 2700K, 3000K, 4000K or 5000K.

CONSTRUCTION > Post is constructed of heavy-wall 6061-T6 aluminum alloy and fixture head is of machined aluminum. Fixture wired with UL listed electrical components for standard Class II low voltage equipment. LED light engine is a self-enclosed assembly with lens, easily replaceable by accessing the face-plate. Wiring for each fixture will include a 36" pigtail to make connection to site wiring, provided by others. Contractor shall provide waterproof connections (waterproof wire nuts are acceptable) and push excess wire and connectors back up into the bollard pole. Base of bollard shall be open and fixture placed over cabling entry as required for a clean installation. All electrical components are installed, wired and 100% tested prior to shipment.

Heavy-duty, 3" wide PVC ground mount stake, included. Both brass insert options provide corrosion-resistant and wear-resistant threads. Choose 10" for most applications; choose 13" to achieve superior anchoring capability *in sandy soil only* (too deep for use with hard soils).

FINISH > Black anodized is standard. Contact factory for other color or finish type.

RATED > Suitable for Wet Location.

WARRANTY > 5 years.



Type: Qty: Project:

SLIMJIM- SLIMJIM

Post

22 22" height OA
30 30" height OA
C-XX" Custom height, specify inches

Color Temperature

27K 2700°K 95CRI
30K 3000°K 95CRI
40K 4000°K 95CRI
50K 5000°K 95CRI

Output

3 12vac/dc 3 watt CREE LED
C___ Custom wattage, consult factory

Distribution

25 25-degree narrow spot beam angle
C___ Client to specify, consult factory

Control

N Non-Dimmable

Finish

BK Anodized Black
CC Custom Color (indicate RAL color)

Mount

GM10 Ground Mount Stake, 10", PVC
GM10B Ground Mount Stake, 10", PVC + brass insert
GM13B Ground Mount Stake, 13", PVC + brass insert

Order Separately:

Exterior Power Supply Box

Enter qty required: PSB004-___FT Exterior wet enclosure, customized for your application. Includes low-voltage driver + lead. Indicate lead length required in feet: _____

