



Type: Qty: Project:

<b>TRI-</b>	<b>TRIFECTA WALL SCENCE</b>	
	<b>Size (Nominal)</b>	
12	12.1" x 10.3" x 9.5",	1.5"D, 8" overall
16	16.1" x 13.7" x 12.7",	2.0"D, 8" overall
20	20.1" x 17.1" x 15.9,	2.5"D, 8" overall
	<b>Color Temperature</b>	
27K	2700°K	
30K	3000°K	
40K	4000°K	
RGBWW	RGBWW	
	<b>Output</b>	
2W	2W	
	<b>Controls</b>	
ELV	ELV	
DMX	DMX	
	<b>Mounting</b>	
STD	Single 'power foot' for in wall wiring.	
CM	Custom Mounting (contact factory)	
	<b>Finish</b>	
BK	Satin Black	
CC	Custom RAL color (consult factory)	

**APPLICATIONS >** The tenacious TRIFECTA is all about form, function and fortitude and achieving all three parameters is no easy task...thus, TRIFECTA! Deceptively delicate and simple in appearance, the mounting legs are actually structural carbon fiber rods for superior durability. Embracing an incongruous design approach, each side length is different, forming an acute scalene triangle. But whether you choose small, medium or large, each bears the same leg span of 61" x 40" for ease of installation. And despite varying shroud depths to gain that 3-D effect (1.5", 2" or 2.5"), all sizes are designed to protrude from the wall by 8" deep for even illumination across an array.

Employ as single unique sconces or make a bold statement by incorporating varying sizes to form a completely custom art installation. Ideal for numerous contemporary applications: Hospitality, Corporate Offices, Hospitals, High-End Residential, Retail, Restaurant and Entertainment Venues.

**LED >** VIVIO™ LED Photon Series offers numerous choices in the latest LED technology. Single Kelvin temperatures range from 2700K to 4000K. Our COB RGBWW (5-in-1 Red-Green-Blue-Double White) provides two additional white LEDs, one warm white and one cool white, achieving a wider color spectrum. 2W, 90+ CRI, Range: 6500K to 2700K, 24V. Requires DMX controls. Contact factory for LED customization.

**CONSTRUCTION >** Light aluminum housing, COB LED light engine, easily replaceable by removing the shroud. Hollow, carbon fiber legs with one "power-foot" for through-wiring into wall. All electrical components are installed, wired and 100% tested prior to shipping.

**MOUNTING >** Surface/wall mounted via miniature "feet". Custom mounting available. Contact factory with unique project specifications.

**FINISH >** Satin black polyester powdercoat finish or custom RAL color.

**RATED >** Suitable for Dry/Damp location only.

**WARRANTY >** 5 years.

